



Bushings, packings and supports



Shaft line bushings with brass external frame. External/internal version in millimetres

Made of hydro-lubricating **rubber**.


Code	Ø A mm	Ø B mm	C mm	Code	Ø A mm	Ø B mm	C mm
52.307.20	20	31,75 (1"1/4)	76.2	52.307.45	45	60,3 (2"3/8)	177.8
52.307.22	22	31,75 (1"1/4)	76.2	52.307.50	50	66,6 (2"5/8)	203.2
52.307.25	25	38,1 (1"1/2)	101.6	52.307.55	55	76,20 (3")	228.6
52.307.26	25	31,75 (1"1/4)	101.6	52.307.60	60	82,5 (3"1/4)	241.3
52.307.28	28	41,27 (1"5/8)	114.3	52.307.65	65	85,72 (3"3/8)	266.7
52.307.30	30	44,4 (1"3/4)	127	52.307.70	70	95,25 (3"3/4)	279.4
52.307.32	32	44,45 (1"3/4)	127	52.307.75	75	101,60 (4")	304.8
52.307.35	35	47,6 (1"7/8)	139.7	52.307.80	80	101,60 (4")	304.8
52.307.38	38	50,80 (2")	152	52.307.85	85	114,30 (4" 1/2)	342.9
52.307.40	40	53,9 (2"1/8)	160	52.307.90	90	114,30 (4" 1/2)	355.6



Shaft line bushings with brass external frame. External/internal version in millimetres

Made of hydro-lubricating **rubber**.


Code	Ø A mm	Ø B mm	Ø C mm	Code	Ø A mm	Ø B mm	Ø C mm
52.308.20	20	30	80	52.308.46	45	65	180
52.308.25	25	35	100	52.308.50	50	66	200
52.308.26	25	40	100	52.308.51	50	70	200
52.308.28	28	38	112	52.308.55	55	73	220
52.308.30	30	40	120	52.308.56	55	75	220
52.308.31	30	45	120	52.308.60	60	78	240
52.308.32	32	45	128	52.308.61	60	80	240
52.308.35	35	48	140	52.308.65	65	83	260
52.308.36	35	50	140	52.308.66	65	85	260
52.308.40	40	55	160	52.308.70	70	90	280
52.308.41	40	56	160	52.308.80	80	100	320
52.308.45	45	61	180	52.308.81	80	102	320



Shaft line bushings with brass external frame. External/internal version in millimetres

Made of hydro-lubricating **rubber**, suitable for US, UK and Australian boats.


Code	Ø A mm	Ø B mm	C mm	Code	Ø A mm	Ø B mm	C mm
52.306.00	1" (25.40)	1"1/4 (31.75)	101.6	52.306.23	1"5/8 (41.27)	2"1/8 (53.97)	165.1
52.306.01	1" (25.40)	1"1/2 (38.10)	101.6	52.306.24	1"7/8 (47.62)	2"5/8 (66.67)	190.5
52.306.02	1"1/4 (31.75)	1"3/4 (44.45)	127	52.306.06	2" 1/4 (57.15)	3" (76.20)	228.6
52.306.03	1"1/2 (38.10)	2" (50.80)	152.4	52.306.08	2" 1/2 (63.50)	3" 1/4 (82.55)	240
52.306.04	1"3/4 (44.45)	2"3/8 (60.32)	177.8	52.306.09	2" 5/8 (66.67)	3" 3/8 (85.72)	266.7
52.306.05	2" (50.80)	2"5/8 (66.67)	203.2	52.306.10	2" 3/4 (69.85)	3" 3/4 (95.25)	279.4
52.306.21	1"1/8 (28.57)	1"5/8 (41.27)	114.7	52.306.12	3" (76.20)	4" (101.60)	304.8
52.306.22	1"3/8 (34.92)	1"7/8 (47.62)	139.7				



Shaft line bushings with resin external frame. External/ internal version in millimetres

Made of **rubber**, hydro-lubricating, fitted with **resin** external plate, ideal for aluminium hulls with aluminium shaft supports.

Code	Ø A mm	Ø B mm	C mm	Code	Ø A mm	Ø B mm	C mm
52.208.25	25	38.10 (1" 1/2)	100	52.208.45	45	60.32 (2" 3/8)	180
52.208.30	30	44.45 (1" 3/4)	120	52.208.50	50	66.67 (2" 5/8)	200
52.208.35	35	47.62 (1" 7/8)	137	52.208.60	60	82.55 (3" 1/4)	240
52.208.40	40	53.97 (2" 1/8)	160				



Shaft line bushings with resin outer frame. Millimeters marked on the indise/ outside.

Made of hydro-lubricating **rubber**.

Code	Ø A mm	Ø B mm	C mm	Code	Ø A mm	Ø B mm	C mm
52.209.25	25	35	100	52.209.40	40	55	160
52.209.26	25	40	100	52.209.41	40	56	160
52.209.30	30	40	120	52.209.45	45	61	180
52.209.31	30	45	120	52.209.46	45	65	180
52.209.35	35	48	160	52.209.55	50	66	200
52.209.36	35	50	160	52.209.56	50	70	200