FORESTI E SUARDI Elettra-t LED courtesy light, recessless version

IP67 **FLUSH MOUNT**

Clear technopolymer body, electro-plated technopolymer snap finish ring. Suitable for mounting on flammable surfaces both horizontally and vertically. Innovative design, Wall Washer light effects. Screw mounting.

Code	V	W	lumen	K	LED beam angle	No of LEDs	Light colour	⟷ mm
13.479.60	12/24	0.48	40	4000	60°x10°	1 SMD LED	white	38x31x10
13.479.61	12/24	0.48	12	-	60°x10°	1 SMD LED	blue	38x31x10

LED courtesy light for recess mounting - frontal orientation

IP55

Translucent polycarbonate body. Stainless steel bezel. Suitable for illuminating steps. Mounting by screws.

Code	Finishing	V	W	lumen	LED beam angle	No of LEDs	Light colour	⟷ mm Ø Recess	Ø external	Overhang
13.181.00	no finish ring	12	0.6	12	24°	3 LED Long Life	yellow	28	46.3x23.3	2.4
13.181.01	Mirror-polished	12	0.6	12	24°	3 LED Long Life	yellow	28	46.3x23.3	2.4
13.181.03	Mirror-polished	12	0.6	7	20°	3 LED Long Life	blue	28	46.3x23.3	2.4

13.181.00

13.181.01



13.181.03

LED courtesy light for recess mounting - frontal orientation

IP67

Polycarbonate body with polished stainless steel front. Mounted with screws.

Code	V	W	lumen	K	LED beam angle	No of LEDs	Light colour	⟷ mm Ø Recess	Ø external	Overhang
13.180.01	12	0.2	36	5000	100°	3 LED Long Life	white	44x16	29x84	3.5
13.180.03	12	0.2	14	-	100°	3 LED Long Life	blue	44x16	29x84	3.5



LED courtesy light, recessless version - frontal orientation

IP67 **FLUSH MOUNT**

Front panel in polished stainless steel. Mounted using screws.

Code	V	W	lumen	K	LED beam angle	No of LEDs	Light colour	⟷ mm Exterior	Overhang
13.178.04	12	1.2	83	5500/6300	120°	6	white	72.5x38	10.5
13.178.03	12	1.2	22	-	120°	6	blue	72.5x38	10.5



Oculus ultra-flat courtesy light - frontal orientation

IP67

Mounts without recess, thickness 5 mm. Watertight casing in technopolymer, with polished stainless steel finishing ring. Mounting via screws.

Code	Model	V	W	lumen	K	LED beam angle	No of LEDs	Light colour	⟷ mm
13.178.10	Front light, SS ring	12	0.3	30	3000	100°	3	white	80x37x5
13.178.14	Perimeter light, SS front panel	12	0.3	30	3000	360°	3	white	78.4x35.4x5
13.178.11	Front light, SS ring	12	0.3	10	-	100°	3	blue	80x37x5
13.178.15	Perimeter light, SS front panel	12	0.3	10	-	360°	3	blue	78.4x35.4x5

13.178.10/11

13.178.14/15



13.178.10/11



13.178.14/15

13.178.xx

LED courtesy light, recessless version - frontal orientation

IP67 **FLUSH MOUNT**

Chromed aluminium housing. Fixing via screws hidden by the front panel.

Code	V	W	lumen	K	LED beam angle	No of LEDs	Light colour	⟷ mm Exterior	Overhang
13.187.01	12	0.4	30	2900-3200	120°	5	white	80x18	15.8
13.187.02	12	0.4	2.4	-	120°	5	blue	80x18	15.8