



**LED courtesy light, recessless version**

IP67 FLUSH MOUNT

Mirror-polished stainless steel finish and polycarbonate diffuser. Fastening by means of screws hidden by the front panel.

Code	Version	V	W	lu-men	K	LED beam angle	No of LEDs	Light colour	mm	
									Exterior	Overhang
13.428.11	Front light	12/24	0.5/1.2	20	3000	110°	3	white	71x15	10
13.428.12	Front light	12/24	0.5/1.2	10	-	110°	3	blue	71x15	10
13.428.01	Downward light	12/24	0.4	20	3000	110°	3	white	71x15	10
13.428.02	Downward light	12/24	0.4	10	-	110°	3	blue	71x15	10
13.428.03	Double up/downward light	12/24	0.6	40	3000	110°	3+3	white	71x15	10
13.428.13	Double up/downward light	12/24	0.6	15	-	110°	3+3	blue	71x15	10

**LED courtesy light, recessless version**

IP67 AISI 316 FLUSH MOUNT

Micro-cast stainless steel casing, mirror-polished. Fixation via screws hidden by the front panel.

Code	Version	V	W	lumen	K	LED beam angle	No of LEDs	Light colour	mm	
									Exterior	Overhang
13.427.11	Front light	12/24	0.6	60	3000	110°	3	white	100x16	11
13.427.12	Front light	12/24	0.6	24	-	110°	3	blue	100x16	11
13.427.32*	Front light	12/24	0.2	60/24	3000	110°	3	White + Blue	100x16	11
13.427.01	Downward light	12/24	0.6	60	3000	110°	3	white	100x16	11
13.427.02	Downward light	12/24	0.6	24	-	110°	3	blue	100x16	11
13.427.22*	Downward light	12/24	0.2	60/24	3000	110°	3	White + Blue	100x16	11
13.427.03	Double up/downward light	12/24	1.2	120	3000	110°	3+3	white	100x16	11
13.427.13	Double up/downward light	12/24	1.2	48	-	110°	3+3	blue	100x16	11

\* Push the switch in sequence to choose the white or blue light.



**FORESTI E SUARDI Andromeda LED courtesy light, recessless version - downward orientation**

IP67 FLUSH MOUNT

Body in transparent technopolymer, front in chromed brass. Suitable for mounting on flammable surfaces. Possibility of fixing with screws both horizontally and vertically. Innovative design and light emission for ambient effects.

Code	V	W	lu-men	K	LED beam angle	No of LEDs	Light colour	mm	
								Exterior	Overhang
13.482.30	12/24	0.5	50	4000	70°	5 x SMD LEDs	white	70x16	11
13.482.31	12/24	0.5	16	-	70°	5 x SMD LEDs	blue	70x16	11
13.482.40	12/24	0.5	50	4000	70°	5 x SMD LEDs	white	100x16	11
13.482.41	12/24	0.5	16	-	70°	5 x SMD LEDs	blue	100x16	11

**Plastic spotlights and ceiling lights**



**Recess-fit or recessless mounting LED ceiling light**

IP67 ABS body. It comes with finish ring also for recessless mounting.

Code	Finishing	V	W	lumen	K	LED beam angle	No of LEDs	Light colour
13.179.56	White	12/24	1.2	75	2900-3200	120°	6	white