


Fans

TMC adjustable fan

Adjustable in all positions, fitted with protection grid. Very efficient model and nice look.

Code	V	Flow rate m ³ /hour	Consumption top speed	Fixing with
16.706.12	12	1000	1.4	2 screws
16.706.24	24	1000	0.7	2 screws



CAFRAMO Bora fan

Fitted with central mounting bracket, built-in handle for easy up/down or side-to-side positioning.

Code	Colour	V	Number of speeds	Blades	Consumption top speed	←→ cm
16.753.12	white	12	3	5" (12.7 cm) ABS	0.24	16.5x24x9
16.754.12	Black	12	3	5" (12.7 cm) ABS	0.24	16.5x24x9
16.753.24	white	24	3	5" (12.7 cm) ABS	0.14	16.5x24x9
16.754.24	Black	24	3	5" (12.7 cm) ABS	0.14	16.5x24x9



CAFRAMO Sirocco II fan

The airflow can be directed in any direction - 360°. The fan can be folded flat and out of the way against the bulkhead when not in use.
12 and 24V operation. Built-in automatic switch off timer after 3, 6, 9 and 12 hours.

Code	Colour	V	Number of speeds	Automatic shutdown timer	Blades	Consumption top speed	←→ cm
16.755.00	white	12/24	3	3,6,9,12 hours	7" (17.8 cm) PE FINGER SAFE	0.35	25x30x7.6
16.755.01	Black	12/24	3	3,6,9,12 hours	7" (17.8 cm) PE FINGER SAFE	0.21	25x30x7.6



CAFRAMO Ultimate fan

Extremely compact. PE blade that does not require a protective grill. Ideal near the station since its motor generates low electrical interference.

Code	Colour	V	Number of speeds	Blades	Consumption top speed	←→ cm
16.751.12	Black	12	2	7" (17.8 cm) PE FINGER SAFE	0.41	18x23x14

