



Boccole, baderne e supporti motore entro bordo



Boccola per linee d'asse con armatura esterna in ottone; versione esterno pollici, interno millimetri

In gomma idrolubrificante.


Codice	Ø A mm	Ø B mm	C mm	Codice	Ø A mm	Ø B mm	C mm
52.307.20	20	31,75 (1"1/4)	76,2	52.307.45	45	60,3 (2"3/8)	177,8
52.307.22	22	31,75 (1"1/4)	76,2	52.307.50	50	66,6 (2"5/8)	203,2
52.307.25	25	38,1 (1"1/2)	101,6	52.307.55	55	76,2 (3")	228,6
52.307.26	25	31,75 (1"1/4)	101,6	52.307.60	60	82,5 (3"1/4)	241,3
52.307.28	28	41,27 (1"5/8)	114,3	52.307.65	65	85,72 (3"3/8)	266,7
52.307.30	30	44,4 (1"3/4)	127	52.307.70	70	95,25 (3"3/4)	279,4
52.307.32	32	44,45 (1"3/4)	127	52.307.75	75	101,60 (4")	304,8
52.307.35	35	47,6 (1"7/8)	139,7	52.307.80	80	101,60 (4")	304,8
52.307.38	38	50,80 (2")	152	52.307.85	85	114,30 (4" 1/2)	342,9
52.307.40	40	53,9 (2"1/8)	160	52.307.90	90	114,30 (4" 1/2)	355,6



Boccola per linee d'asse con armatura esterna in ottone; versione esterno/ interno in millimetri

In gomma idrolubrificante.


Codice	Ø A mm	Ø B mm	Ø C mm	Codice	Ø A mm	Ø B mm	Ø C mm
52.308.20	20	30	80	52.308.46	45	65	180
52.308.25	25	35	100	52.308.50	50	66	200
52.308.26	25	40	100	52.308.51	50	70	200
52.308.28	28	38	112	52.308.55	55	73	220
52.308.30	30	40	120	52.308.56	55	75	220
52.308.31	30	45	120	52.308.60	60	78	240
52.308.32	32	45	128	52.308.61	60	80	240
52.308.35	35	48	140	52.308.65	65	83	260
52.308.36	35	50	140	52.308.66	65	85	260
52.308.40	40	55	160	52.308.70	70	90	280
52.308.41	40	56	160	52.308.80	80	100	320
52.308.45	45	61	180	52.308.81	80	102	320



Boccola per linee d'asse con armatura esterna in ottone; versione esterno/ interno in pollici

In gomma idrolubrificante; per scafi di provenienza Stati Uniti, Inghilterra e Australia.


Codice	Ø A mm	Ø B mm	C mm	Codice	Ø A mm	Ø B mm	C mm
52.306.00	1" (25,40)	1"1/4 (31,75)	101,6	52.306.23	1"5/8 (41,27)	2"1/8 (53,97)	165,1
52.306.01	1" (25,40)	1"1/2 (38,10)	101,6	52.306.24	1"7/8 (47,62)	2"5/8 (66,67)	190,5
52.306.02	1"1/4 (31,75)	1"3/4 (44,45)	127	52.306.06	2" 1/4 (57,15)	3" (76,20)	228,6
52.306.03	1"1/2 (38,10)	2" (50,80)	152,4	52.306.08	2" 1/2 (63,50)	3" 1/4 (82,55)	240
52.306.04	1"3/4 (44,45)	2"3/8 (60,32)	177,8	52.306.09	2" 5/8 (66,67)	3" 3/8 (85,72)	266,7
52.306.05	2" (50,80)	2"5/8 (66,67)	203,2	52.306.10	2" 3/4 (69,85)	3" 3/4 (95,25)	279,4
52.306.21	1"1/8 (28,57)	1"5/8 (41,27)	114,7	52.306.12	3" (76,20)	4" (101,60)	304,8
52.306.22	1"3/8 (34,92)	1"7/8 (47,62)	139,7				



Boccola per linee d'asse con armatura esterna in resina; versione esterno/ interno in millimetri

In gomma idrolubrificante; per scafi in alluminio con supporti asse in alluminio.

Codice	Ø A mm	Ø B mm	C mm	Codice	Ø A mm	Ø B mm	C mm
52.208.25	25	38,10 (1" 1/2)	100	52.208.45	45	60,32 (2" 3/8)	180
52.208.30	30	44,45 (1" 3/4)	120	52.208.50	50	66,67 (2" 5/8)	200
52.208.35	35	47,62 (1" 7/8)	137	52.208.60	60	82,55 (3" 1/4)	240
52.208.40	40	53,97 (2" 1/8)	160				



Boccole per linee d'asse con armatura esterna in resina esterno/ interno in millimetri

In gomma idrolubrificante.

Codice	Ø A mm	Ø B mm	C mm	Codice	Ø A mm	Ø B mm	C mm
52.209.25	25	35	100	52.209.40	40	55	160
52.209.26	25	40	100	52.209.41	40	56	160
52.209.30	30	40	120	52.209.45	45	61	180
52.209.31	30	45	120	52.209.46	45	65	180
52.209.35	35	48	160	52.209.55	50	66	200
52.209.36	35	50	160	52.209.56	50	70	200